# **§MAVERICK™ TRAIL DPS™ 800 T**

### AGILE

- · Sturdy engine and transmission
- Easy Handling and capabilities
- Front and rear suspension designed for trail riding

### **ADVENTUROUS**

- Meaningful functionalities and versatilities
- Enhanced comfort with Ergo-Lok cockpit
- Build your Maverick Trail that fits your needs

### CONFIDENT

- · Can-Am design and proven fit & finish
- **Enhanced** protection
- More adventure and less maintenance

## SPECIFIC TO DPS PACKAGE

- Dynamic Power Steering (DPS™)
- Dynamic Brake and Traction Control System
- Lockable rear differential
- SPORT / ECO™ modes
- 12-in. cast-aluminum wheels
- Ergoprint seats with color accent
- Unique Can-Am LED signature



Can-Am Red

800
55 hp, Rotax® 799.9 cc, V-twin, liquid cooled
Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection  Extra-L / H / N / R / P
Selectable 2WD / 4WD with lockable rear differential
Brake and Traction Control System SPORT / ECO™ modes
Dynamic Power Steering (DPS)
More than 60 km/h

SUSPENSIONS	
Front Suspension	Double A-arm with sway bar 25.4 cm travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	TTA with sway bar 26.7 cm travel
Rear Shocks	Twin tube gas charged shocks

BRAKES	
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
ABS	Standard

TIRES / WHEEL	S
Front Tires	Carlisle ACT 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle ACT 26 x 9 x 12 in. (66 x 22.9 x 30.5 cm)
Wheels	12-in (30.5 cm) cast-aluminum

<b>DIMENSIONS</b> A	CAPACITIES
LxWxH	300.5 x 157.8 x 175.5 cm
Wheelbase	230.1 cm
Ground Clearance	25.4 cm
Dry Weight	603.7 kg
Cage	ROPS-approved profiled cage. Certified ISO 3471.
Cargo Box Capacity	136 kg
Storage Capacity	Total: 20.2 L Glove Box: 15.6 L Driver storage: 1.5 L Center console and Cup holders: 3.1 L
Towing capacity	680 kg

ont	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers	Towing capacity	680 kg
ar	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers	Fuel Capacity	38 L
S	Standard		

FEATURES			
Gauge	7.6 in. (19.3 cm) wide digital display with keypad	Winch	Prewired for available winch
		Steering Wheel	Adjustable tilt steering
Instrumentation	Lighter type DC outlet in console (20-A)	Protection	Integrated front steel bumper, injected full body skid
Magneto	650W		plates, mudguards, mudflaps
Lighting	Two 55 W reflectors with LED tail light	Hitch Type	2-in. hitch receiver with tow ball, 7-pin trailer connection (12V)
T-category features	Horn, flashers and position lamps, mirrors, hook on front metal bumper		

WARRANTY		
Factory	2 years	



